

Test summary of UN test for Lithium ion single cell battery

Customer Model : D181A, WW
 Product Code : F12432978
 Product Name : 1UR18650R-N008F
 Manufacturer : Panasonic Energy Co., Ltd.

H. Kuroda Senior Manager
 Development Promotion Department
 System Development Division
 Panasonic Energy Co., Ltd.

: 222-1 Kaminaizen, Sumoto City, Hyogo 656-8555, Japan
 Tel +81-799-24-4111, email un_38_lib@ml.jp.panasonic.com
<https://industrial.panasonic.com/ww/products/batteries/>

Test Laboratory : Same as the manufacturer

We declare that this battery passed UN test.

Manual of Tests and Criteria (38.3 Lithium batteries)		Test results	Note	Number of test batteries/cells
No.	Test item			
T 1	Altitude simulation	Pass		First cycle fully charged 10 cells
T 2	Thermal test	Pass		
T 3	Vibration	Pass		
T 4	Shock	Pass		
T 5	External short circuit	Pass		
T 6	Crush	Pass		First cycle 50% charged 5 cells
T 7	Overcharge	Pass		First cycle, fully charged 4 batteries
T 8	Forced discharge	Pass		First cycle, fully discharged 10 cells

*1 The test data may contain additional test result other than above table.

Lithium ion single cell battery Specification

Item	Value/Description	Note
Watt-hour rating / Rated capacity	6.7 Wh / 1.86 Ah	Number of cells: 1
Nominal voltage	3.6 V	
Weight	max. 60 g	
Physical description	Battery with shrink tube	

Above test procedures are compliant to the following manual.

(Manual of Tests and Criteria ST/SG/AC.10/11, PartIII, sub-section 38.3, Rev.5A1 for cell, Rev.5A1 for battery)

Judgment for necessity of test items is carried out based on the latest rules, and it is not linked with the version actually tested.

Certificate of Package Test for Lithium ion single cell battery

Customer Model : D181A, WW
Product Code : F12432978
Product Name : 1UR18650R-N008F
Manufacturer :

Panasonic Energy Co., Ltd. 222-1 Kaminaizen, Sumoto City, Hyogo 656-8555, Japan
Tel +81-799-24-4111, email un_38_lib@ml.jp.panasonic.com
<https://industrial.panasonic.com/ww/products/batteries/>

H. Kuroda Senior Manager
Development Promotion Department
System Development Division
Panasonic Energy Co., Ltd.

Test Laboratory : Same as the manufacturer

We declare that this battery passed UN test.

Test item	Test results	Note
Drop Test	Pass	The package shall be dropped from 1.2m high on to a concrete surface (flat and horizontal) with five orientations (drop once a sample) ; (1) flat on the bottom, (2) flat on the long side, (3) flat on the short side, (4) on the edge, (5) on the corner

Lithium ion single cell battery Specification

Item	Nominal value	Note
Watt-hour rating / Rated capacity	6.7 Wh / 1.86 Ah	
Nominal voltage	3.6 V	

Above test procedures are compliant to the following regulation.
(Model Regulations ST/SG/AC.10/1/Rev.22, Special Provision188)