



---

## CW9162 Datasheet

---

# Ultra-High Performance Wi-Fi 6E Wireless

Tri-band 802.11ax-compatible access point with separate radios dedicated to security, RF management, and Bluetooth® coupled with a USB port for hardware peripherals including third-party solutions.



---

## Flexible Deployment Options

With the flexibility to choose between cloud- and on-premises management, the Catalyst 9162 Series Access Point ensures network investment protection and unlocks the power of hybrid work. The Wi-Fi 6E-compliant access point takes advantage of the 6-GHz band expansion to produce a network that is more reliable and secure, with higher throughput, more capacity, and less device interference. The access points come with three 2x2 client serving Wi-Fi radios and provide

---

a host of cutting-edge features.

With the industry's leading network architecture - Catalyst joining the industry's leading cloud IT platform - Meraki, this access point provides an unparalleled network experience. For organizations that need solutions to power hybrid work, and that allow their people to work anywhere at any given time with elevated, secure, and connected experiences, the Cisco Catalyst 9162 Series Access Points are the best choice.

Operational management is not static, as customers are able to change their network management whenever they want. If a network with Cisco Catalyst 9162 Series Access Points was originally an on-premises deployment, it can be changed to cloud-based management without the need to purchase and redistribute additional hardware.

## Cisco Meraki Cloud Management

Pairing the Cisco Catalyst 9162 access points with the Meraki cloud platform gives organizations a unified IT experience for network monitoring and management. The Meraki dashboard provides an intuitive and interactive web interface connecting your network to the industry's leading cloud IT platform.

Through the dashboard, Meraki provides sophisticated and scalable tools to automate network optimization, deploy policy and segmentation configurations across thousands of sites and devices, and manage a full-stack network from SD-WAN to Access to IoT technologies. The platform supports over 3.9 million active networks around the world.

Working together, the Catalyst 9162 Series and Cisco Meraki offer such features as:

- Cisco DNA Spaces
- Cisco Identity Services Engine
- Meraki Health intelligent optimization and assurance
- Meraki Vision, smart cameras, and sensors for network closet monitoring

## Cisco DNA Center and Catalyst 9800 WLC support

Cisco Catalyst 9162 Series Access Points can also be paired with Catalyst 9800 WLC and Cisco DNA Center. Cisco DNA Center allows you to understand your network with real-time analytics, quickly detect and contain security threats, and easily provide network-wide consistency through automation and virtualization.

Working together, the Catalyst 9162 Series and Cisco DNA offer such integrations and solutions as:

- Cisco DNA Spaces
- Cisco Identity Services Engine
- Cisco DNA Analytics and Assurance along with Intelligence Capture

For information about Cisco DNA, refer to the [Cisco DNA Solution Overview](#).

---

## CW9162 and Meraki cloud management

Management of the CW9162 is through the Meraki cloud, with an intuitive browser-based interface that enables rapid deployment without time-consuming deployment complexity and time-consuming staging process. Since the CW9162 is self-configuring and managed over the web, it can be deployed at a remote location in a matter of minutes, even without on-site IT staff.

24x7 monitoring via the Meraki cloud delivers real-time alerts if the network encounters problems. Remote diagnostic tools enable immediate troubleshooting over the web so that distributed networks can be managed with a minimum of hassle.

The CW9162's firmware is automatically kept up to date via the cloud. New features, bug fixes, and enhancements are delivered seamlessly over the web. This means no manual software updates to download or missing security patches to worry about.

---

## Product Highlights

- 2x2:2 MU-MIMO 802.11ax compatible
- ~3.9 Gbps tri-radio aggregate frame rate
- 24x7 real-time WIDS/WIPS and spectrum analytics via dedicated Scanning radio
- Integrated Bluetooth Low Energy Beacon and scanning radio
- 1 x 2.5 Gbps mGig Ethernet port support
- USB 2.0 host interface (Type A connector) with 4.5W power budget
- Enhanced transmit power and receive sensitivity
- Full-time Wi-Fi location tracking via dedicated Scanning radio
- Integrated enterprise security and guest access
- Application-aware traffic shaping
- Optimized for voice and video
- Self-configuring, plug-and-play deployment
- Sleek design blends into office environments

---

## Features

### Tri-radio aggregate frame rate of up to ~3.9 Gbps\*

A 6 GHz 2x2:2, 5 GHz 2x2:2 and 2.4 GHz 2x2:2 radio offer a combined tri-radio aggregate frame rate of ~3.9 Gbps\*. Technologies like transmit beamforming and enhanced receive sensitivity allow the CW9162 to support a higher client density than typical enterprise-class access points, resulting in better performance for more clients from each AP.



\* Refers to maximum over-the-air data frame rate capability of the radio chipset, and may exceed data rates allowed by IEEE 802.11ax operation.

### Multi-User Multiple Input Multiple Output (MU-MIMO)

With support for features of 802.11ax, the CW9162 offers DL MU-MIMO and OFDMA for more efficient transmission to multiple clients. Especially suited to environments with numerous mobile devices, MU-MIMO and OFDMA enable multiple clients to receive data simultaneously. This increases the total network performance and improves the end-user experience.

### IoT and Bluetooth Low Energy Radio

An integrated Bluetooth radio provides seamless deployment of BLE Beacon functionality and effortless visibility of Bluetooth devices. The CW9162 enables the next generation of location-aware applications while future-proofing deployments, ensuring it's ready for any new customer engagement strategies.

### Automatic cloud-based RF Optimization

The CW9162's sophisticated and automated RF optimization means that there is no need for the dedicated hardware and RF expertise typically required to tune a wireless network. The RF data collected by the dedicated fourth radio is continuously fed back to the Meraki cloud. This data is then used to automatically tune the channel selection, transmit power, and client connection settings for optimal performance under even the most challenging RF conditions.

### Integrated Enterprise Security and Guest Access

The CW9162 features integrated, easy-to-use security technologies to provide secure connectivity for employees and guests alike. Advanced security features such as AES hardware-based encryption and Enterprise authentication with 802.1X and Active Directory integration provide wired-like security while still being easy to configure. CW9162 will also support 192-bit encryption along with WPA3 support for added security of the wireless network.

One-click guest isolation provides secure, Internet-only access for visitors. PCI compliance reports check network settings against PCI requirements to simplify

secure retail deployments.

### Dedicated scanning radio delivers 24x7 Air Marshal and RF analytics

There's no need to choose between wireless security (AirMarshal), advanced RF analysis, and serving client data. A dedicated scanning radio means that all functions occur in real-time, without any impact on client traffic or AP throughput.

The CW9162's dedicated tri-band scanning radio security radio continually monitors the environment, characterizing RF interference and containing wireless threats like rogue access points. Containment is only possible in the 2.4 GHz and 5 GHz frequencies as 6 GHz requires Protected Management Frames (PMF).

### Enterprise Mobility Management (EMM) & Mobile Device Management (MDM) integration

Meraki Systems Manager natively integrates with the CW9162 to offer automatic, context-aware security. System Manager's self-service enrollment helps to rapidly deploy MDM without installing additional equipment and then dynamically tie firewall and traffic shaping policies to client posture.

### Application-aware traffic shaping

The CW9162 includes an integrated layer 7 packet inspection, classification, and control engine, enabling the configuration of QoS policies based on traffic type, helping to prioritize mission-critical applications while setting limits on recreational traffic like peer-to-peer and video streaming. Policies can be implemented per network, SSID, user group, or individual user for maximum flexibility and control.

### Voice and video optimizations

Industry-standard QoS features are built-in and easy to configure. Wireless Multimedia (WMM) access categories, 802.1p, and DSCP standards support all ensure important applications get prioritized correctly, not only on the CW9162 but also on other network devices on. Unscheduled Automatic Power Save Delivery (U-APSD) and Target Wait Time feature in 802.11ax clients ensure minimal battery drain on wireless VoIP phones.

### Self-configuring, self-maintaining, always up-to-date

When plugged in, the CW9162 automatically connects to the Meraki cloud, downloads its configuration, and joins the appropriate network. Administrators can schedule automatic firmware upgrades for their Dashboard network seamlessly. This ensures the network is kept up-to-date with bug fixes, security updates, and new features.

### Meraki Health

CW9162 will support all the latest and greatest analytics to provide AI/ML anomaly detection, server root cause analysis, wireless client scoring based on performance and connectivity metrics, and network benchmarking for networks of similar size and vertical. Along with these features, CW9162 will provide advanced location analytics via API and graphs in Dashboard to provide a clear picture of client density and their movement across the floor plan.

### Choice of Management mode

Cisco Catalyst 9162 Series Access Points can be managed either on-premises with Catalyst 9800 Wireless Lan Controllers (WLC) or cloud-managed through the Meraki dashboard. Customers have the flexibility to deploy these access points in one mode and migrate to the other mode in the future.

---

## Specifications

| Category | Specifications |
|----------|----------------|
|----------|----------------|

## Radios

- 2.4 GHz 802.11b/g/n/ax client access radio
- 5 GHz 802.11a/n/ac/ax client access radio
- 6 GHz 802.11ax client access radio
- 2.4 GHz, 5 GHz, and 6 GHz tri-band Air Marshal WIDS/WIPS, spectrum analysis, & location analytics radio
- 2.4 GHz Bluetooth Low Energy (BLE) radio with Beacon and BLE scanning support
- Concurrent operation of all five radios

## Antenna

- Integrated omni-directional antennas
  - 2.4 GHz: Peak gain 4 dBi, internal antenna, omnidirectional in azimuth
  - 5 GHz: Peak gain 5 dBi, internal antenna, omnidirectional in azimuth
  - 6 GHz: Peak gain 5 dBi, internal antenna, omnidirectional in azimuth

## 802.11 ax compatible, 802.11ac Wave 2 and 802.11n Capabilities

- UL/DL-OFDMA
- Target Wait Time (TWT)
- BSS coloring\*
- SU-MIMO and DL MU-MIMO support
- Maximal ratio combining (MRC)
- 802.11ax beamforming
- 20 and 40 MHz\* channels (802.11n)
- 20, 40\*, 80 MHz channels (802.11ac Wave 2)
- 20, 40\*, 80 and 160MHz channels (802.11ax)



**Note:** \*40MHz channels are supported only in 5 & 6 GHz bands.

- Up to 1024-QAM on 2.4 GHz, 5 GHz and 6 GHz bands
- Packet aggregation - A-MPDU (transmit and receive), A-MSDU (transmit and receive)

## Power

- Power over Ethernet: 37 - 42.5 V (802.3at compliant)
- DC Power Adapter (12V)
- Power consumption: Up to 30W
- Minimum power requirement: 30W (802.3at complaint)
- Power over Ethernet injector and DC adapter sold separately



Actual power consumption may vary depending on the AP usage

## Interfaces

- 1x 100/1000/2.5G BASE-T Ethernet (RJ45)
- 1x DC power connector (5.5 mm, center positive)
- USB 2.0 at 4.5W (with 802.3at power)



- Console - Only available in DNA Mode

## Mounting

- All Cisco standard mounting hardware supported (AIR-AP-BRACKET-2 included)
- Desktop, ceiling, and wall mount capable
- Ceiling tile rail (9/16, 15/16, or 1 1/2" flush or recessed rails), assorted cable junction boxes

## Physical security

- Two security screw options (included) (13.5 mm long and 2.5 mm diameter and 5 mm head)
- Kensington lock

## Environment

- Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C)
- Nonoperating (storage) altitude test: 25°C (77°F) at 15,000 ft (4600 m)
- Operating temperature: 32° to 122°F (0° to 50°C)
- Operating humidity: 10% to 90% (non-condensing)
- Operating altitude test: 40°C (104°F) at 9843 ft (3000 m)

## Reliability

Mean Time Between Failure (MTBF):

- 2,370,107 hrs at 77°F (25°C) operating temperature
- 991,862 hrs at 113°F (45°C) operating temperature

## Physical Dimensions

- 7.8 x 7.8 x 1.7 in. (200 x 200 x 44.45 mm)
- Weight: 2.05 lb. (0.93 kg)

## Security

- Integrated Layer 7 firewall with mobile device policy management

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                             | <ul style="list-style-type: none"> <li>• Real-time WIDS/WIPS with alerting and automatic rogue AP containment with Air Marshal</li> <li>• Flexible guest access with device isolation</li> <li>• VLAN tagging (802.1q) and tunneling with IPsec VPN</li> <li>• PCI compliance reporting</li> <li>• WPA2-PSK, WPA2-Enterprise, WPA3 - Personal, WPA3 - Enterprise, WPA3 - Enhanced Open (OWE)</li> <li>• EAP Local Authentication - EAP-TTLS/PAP/ PEAP-GTC, EAP-TLS</li> <li>• AES encryption</li> <li>• Enterprise Mobility Management (EMM) &amp; Mobile Device Management (MDM) integration</li> <li>• Cisco ISE integration for Guest access and BYOD Posturing</li> </ul> |
| <b>Quality of Service</b>   | <ul style="list-style-type: none"> <li>• Advanced Power Save (U-APSD)</li> <li>• WMM Access Categories with DSCP and 802.1p support</li> <li>• Layer 7 application traffic identification and shaping</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Mobility</b>             | <ul style="list-style-type: none"> <li>• PMK, OKC, &amp; 802.11r for fast Layer 2 roaming</li> <li>• Distributed or centralized layer 3 roaming</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Analytics</b>            | <ul style="list-style-type: none"> <li>• Embedded location analytics reporting and device tracking</li> <li>• Global L7 traffic analytics reporting per network, per device, &amp; per application</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>LED Indicators</b>       | <ul style="list-style-type: none"> <li>• One power/booting/firmware upgrade status</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Regulatory</b>           | <ul style="list-style-type: none"> <li>• RoHS</li> <li>• For additional country-specific regulatory information, please contact Meraki sales</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Warranty</b>             | <ul style="list-style-type: none"> <li>• Indoor access point</li> <li>• Lifetime hardware warranty with advanced replacement included</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Ordering Information</b> | <ul style="list-style-type: none"> <li>• CW9162I-MR: Catalyst CW9162I Cloud Managed 802.11ax Compatible AP</li> <li>• MA-PWR-30W-XX: Meraki AC Adapter for MR Series</li> <li>• MA-INJ-6: Meraki Multigigabit 802.3bt Power over Ethernet Injector (power cable separate SKU)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                      |

- Cisco AIR-PWRINJ-6 802.3at
- Cisco AIR-PWRINJ-7 802.3bt



Cisco AIR-PWRINJ-6 802.3at power cord - MA-PWR-CORD-XX (XX Country Code) should be ordered separately for the AC adapter and Ethernet injector

- Mounting bracket: AIR-AP-BRACKET-1 and AIR-AP-BRACKET-2(bundled)
- Meraki access point license required



Software features can be enabled via firmware updates

## Compliance and Standards

| Category         | Standard                                                                                       |
|------------------|------------------------------------------------------------------------------------------------|
| IEEE Standards   | • 802.3 ab/bz                                                                                  |
|                  | • 802.3at                                                                                      |
|                  | • 802.11a/b/g/n/ac/ax                                                                          |
|                  | • 802.11d/h/i/k/r/u/v/w                                                                        |
| Certifications   | • <b>Wi-Fi Alliance:</b> Wi-Fi 6 (R2), Wi-Fi 6E, WPA3-R3, WPA3-Suite B, Enhanced Open Security |
|                  | • <b>Bluetooth SIG:</b> Bluetooth Low Energy                                                   |
| Safety Approvals | • CSA and CB 60950 & 62368                                                                     |
|                  | • EN 60601 certified                                                                           |
|                  | • Conforms to UL 2043 (Plenum Rating)                                                          |
| Radio Approvals  | • FCC Part 15C                                                                                 |
|                  | • 15E RSS-247 (Canada)                                                                         |
|                  | • EN 300 328 ( v2.1.1)                                                                         |
|                  | • EN 301 893 (v2.1.1)                                                                          |
|                  | • AS/NZS 4268 (Australia/NZ)                                                                   |
|                  | • NOM-121 (Mexico)                                                                             |

- NCC LP0002 (Taiwan)



For additional country-specific regulatory information, please contact Meraki sales

#### EMI Approvals (Class B)

- FCC Part 15B
- ICES-003 (Canada)
- EN 301 489-1-17
- EN 55032
- EN 55024 (Europe)
- CISPR 32 (Australia/NZ) VCCI (Japan)

#### Exposure Approvals

- FCC Part 2 RSS-102 (Canada)
- EN 50385
- EN 6231
- EN 62479 (Europe)
- AS/NZS 2772 (Australia/NZ)

## Context and Comparisons

### 802.11ax, 802.11ac Wave 2 and 802.11n Capabilities

| MR36                                                                           | MR44                                                                           | MR56                                                                            | CW9162                                                                        |
|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| DL-OFDMA, UL-OFDMA, TWT support**, BSS coloring**                              | DL-OFDMA, UL-OFDMA, TWT support**, BSS coloring**                              | DL-OFDMA, UL-OFDMA, TWT support**, BSS coloring**                               | DL-OFDMA, UL-OFDMA, TWT support**, BSS coloring**                             |
| 2.4 GHz: 2 x 2 multiple input, multiple output (MIMO) with two spatial streams | 2.4GHz: 4 x 4 multiple input, multiple output (MIMO) with four spatial streams | 2.4 GHz: 4 x 4 multiple input, multiple output (MIMO) with four spatial streams | 2.4 GHz 2 x 2 multiple input, multiple output (MIMO) with two spatial streams |
| 5 GHz: 2 x 2 multiple input, multiple output (MIMO) with four spatial streams  | 5 GHz: 4 x 4 multiple input, multiple output (MIMO) with four spatial streams  | 5 GHz: 8 x 8 multiple input, multiple output (MIMO) with eight spatial streams  | 5 GHz: 2 x 2 multiple input, multiple output (MIMO) with two spatial streams  |

|                                                                                                                                                                        |                                                                                                                           |                                                                                                                           |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                        |                                                                                                                           |                                                                                                                           | 6 GHz: 2 x 2 multiple input, multiple output (MIMO) with two spatial streams                                                     |
| Maximal ratio combining (MRC) & beamforming                                                                                                                            | Maximal ratio combining (MRC) & beamforming                                                                               | Maximal ratio combining (MRC) & beamforming                                                                               | Maximal ratio combining (MRC) & beamforming                                                                                      |
| SU-MIMO, UL MU-MIMO and DL MU-MIMO support                                                                                                                             | SU-MIMO, UL MU-MIMO and DL MU-MIMO support                                                                                | SU-MIMO, UL MU-MIMO and DL MU-MIMO support                                                                                | SU-MIMO, UL MU-MIMO and DL MU-MIMO support                                                                                       |
| 20 and 40 MHz* channels (802.11n); 20, 40*, and 80 MHz channels (802.11ac Wave 2); 20, 40* and 80 MHz channels (802.11ax)                                              | 20 and 40 MHz* channels (802.11n); 20, 40*, and 80 MHz channels (802.11ac Wave 2); 20, 40* and 80 MHz channels (802.11ax) | 20 and 40 MHz* channels (802.11n); 20, 40*, and 80 MHz channels (802.11ac Wave 2); 20, 40* and 80 MHz channels (802.11ax) | 20 and 40 MHz* channels (802.11n); 20, 40*, and 80 MHz channels (802.11ac Wave 2); 20, 40*, 80MHz and 160MHz channels (802.11ax) |
| <div>  <b>Note:</b> *40MHz channels are supported only in 5 &amp; 6 GHz bands. </div> |                                                                                                                           |                                                                                                                           |                                                                                                                                  |
| Up to 1024-QAM on both 2.4 GHz & 5 GHz bands                                                                                                                           | Up to 1024-QAM on both 2.4 GHz & 5 GHz bands                                                                              | Up to 1024-QAM on both 2.4 GHz & 5 GHz bands                                                                              | Up to 1024-QAM on all three - 2.4 GHz, 5 GHz and 6 GHz bands                                                                     |
| Packet aggregation                                                                                                                                                     | Packet aggregation                                                                                                        | Packet aggregation                                                                                                        | Packet aggregation                                                                                                               |

## Power

| MR36                                                        | MR46                                                                                         | MR56                                                        | CW9162                                                      |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------------------|-------------------------------------------------------------|
| Power over Ethernet: 37 - 57 V (802.af compliant)           | Power over Ethernet: 42.5 - 57 V (802.3at) <b>or</b> 37 - 57 V (802.3af) - low power mode ** | Power over Ethernet: 42.5 - 57 V (802.3at compliant)        | Power over Ethernet: 42.5 - 57 V (802.3at compliant)        |
| Alternative: 12 V DC input                                  | Alternative: 12 V DC input                                                                   | Alternative: 12 V DC input                                  | Alternative: 12 V DC input                                  |
| Power consumption: 15W max (802.3af)                        | Power consumption: 30W max (802.3at) <b>or</b> 15W max (802.3af) - low power mode **         | Power consumption: 30W max (802.3at <b>required</b> )       | Power consumption: 30W max (802.3at <b>required</b> )       |
| Power over Ethernet injector and DC adapter sold separately | Power over Ethernet injector and DC adapter sold separately                                  | Power over Ethernet injector and DC adapter sold separately | Power over Ethernet injector and DC adapter sold separately |



\*\* features can be enabled via future firmware updates

## Interfaces

| MR36                                                     | MR46                                                     | MR56                                                     | CW9162                                          |
|----------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|-------------------------------------------------|
| 1x 100/1000 BASE-T Ethernet (RJ45)                       | 1x 100/1000/2.5G BASE-T Ethernet (RJ45)                  | 1x 100/1000/2.5G/5G BASE-T Ethernet (RJ45)               | 1x 100/1000/2.5G BASE-T Ethernet (RJ45)         |
| 1x DC power connector (5.5 mm x 2.5 mm, center positive) | 1x DC power connector (5.5 mm x 2.5 mm, center positive) | 1x DC power connector (5.5 mm x 2.5 mm, center positive) | 1x DC power connector (5.5 mm, center positive) |

## Physical Dimensions


| MR36                                                                                         | MR46                                                                        | MR56                                                                         | CW9162                                                               |
|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|------------------------------------------------------------------------------|----------------------------------------------------------------------|
| 9.84" x 4.72" x 1.42" (25 cm x 12 cm x 3.6 cm), not including desk mount feet or mount plate | 12.05" x 5.06" x 1.74" (306.0 x 128.4 x 44.3 mm), not including mount plate | 12.83" x 5.54" x 1.76" (326.0 x 140.79 x 44.7 mm), not including mount plate | 7.8" x 7.8" x 1.7" 200 x 200 x 45.45 mm) , not including mount plate |
| Weight: 17.35 oz (492 g)                                                                     | Weight: 28.22 oz (0.800 kg)                                                 | Weight: 35.27 oz (1 kg)                                                      | Weight: 2.05 lbs (0.93 kg)                                           |

## Signal Coverage Pattern


## Client Serving Radios

### 6 GHz Radio

**Catalyst 9162I Series Wi-Fi 6E Access Points**  
6 GHz - Azimuth - Client Serving - Normalized




**Catalyst 9162I Series Wi-Fi 6E Access Points**  
6 GHz - Elevation - Client Serving - Normalized



5 GHz Radio


Catalyst 9162I Series Wi-Fi 6E Access Points

5 GHz - Azimuth - Client Serving - Normalized




## Catalyst 9162I Series Wi-Fi 6E Access Points

5 GHz - Elevation - Client Serving - Normalized




2.4 GHz Radio


**Catalyst 9162I Series Wi-Fi 6E Access Points**  
2.4 GHz - Azimuth - Client Serving - Normalized



**Catalyst 9162I Series Wi-Fi 6E Access Points**  
**2.4 GHz - Elevation - Client Serving - Normalized**



IoT Radios



**Catalyst 9162I Series Wi-Fi 6E Access Points**  
**2.4 GHz - Elevation - IoT Radio - Normalized**

