IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

Name/Description of battery							
1. Name/Description of battery							
1a. Name/Desc	ription of the cells inside t	the batteru					
101 11011107 2000	prion or the conto more	5 5 5 6 6 7					
The test summar	u of the cells inside the hat	tery must either be presented or und	der checknoint 9 and 9a i	t must			
be confirmed tha	t the UN 38.3 test summar	ry for the cells is available.	aci checkpoint o dha oa i	t mast			
2. Manufacture	er of battery						
Name							
Address							
Phone							
Email							
Website							
2a. Manufacture	er of the equipment (if the t	battery is contained in equipment)					
Name							
Address							
Phone	Phone						
Email	mail mail						
Website	Website						
3. Test laborate	ory of battery						
Name							
Address							
Phone							
Email							
Website							
4. ID-number a	and date						
Unique test repo	ort identification number	Date of test report					



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)					

#### **DESCRIPTION OF BATTERY**

5. Mark the type of battery with an "•"							
	Lithium ion battery	Lithium metal battery					
	Lithium hybrid battery						
6. Pa	rameters						
Mass	in gram (g):						
Lithiu	m ion: Indicate watt-hour rating (Wh):						
Lithium metal: Indicate lithium metal content in gram (g):							
<b>Lithium hybrid:</b> Indicate lithium metal content in gram (g) and watt-hour rating (Wh):							
Extriction rigidita. Indicate during metal content in grain (g) and water hour fatting (VVII).							
7. Physical description of battery							
7. 11	igation description of battery						
8. Model numbers							

#### TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "●"	N/A	pass	fail
T1 - Altitude simulation			
T2 - Thermal Test			
T3 - Vibration			
T4 - Shock			
T5 - External Short Circuit			
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.			
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.			
T7 - Overcharge			
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.			



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

9a.UN 38.3 Test Confirmation for the Cells inside the battery

When no separate document for the cells is provided, this confirms that

Name/Description of battery (taken from field 1)

Cell

Cell

the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" needs to be ticked.	-	ι 38.3 Te Ifirmed	st	N 38.3	Test NOT rmed	
10. Reference to assembled battery testing requirements						
10. Reference to assembled battery testing requirements						
					N/A	
11. Reference to the revised edition of the Manual of Tests and Criteria used and	to am	endmenl	ts ther	eto		
ADDITIONAL SUPPLIER INQUIRY						
12. Quality management system for manufacturing batteries  Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?				YES	NO	
13. Are the following parameters exceeded?  Lithium ion battery: more than 100 Wh  Lithium metal battery: more than 2 g Lithium  Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh				YES	NO	
Check point 14 – 16 need to be answered when 13 has been ticked "YES":						
<b>14.</b> Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?				YES	NO	
15. Is each battery equipped with an effective means of preventing external short circuits?				YES	NO	
<b>16.</b> Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?		N/A		YES	NO	
17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batterie	s and	lithium p	olyme	er batte	ries	
State of Charge (SoC) max. 30 %		N/A		YES	NO	

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)	

#### BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:						
18.a) Only button cells enclosed?			YES	NO		
18.b) Number of enclosed batteries per equipment						
When the equipment is intentionally active/switched on during transport e.g. data loggers:						
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment N/A YES				NO		
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160		N/A		YES	NO	

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature				