

## Safe-IT USB 2.0 A to B Antibacterial Cable (M/M), White, 10 ft. (3.05 m)

MODEL NUMBER: U022AB-010-WH



USB cable built with antibacterial material connects low- and high-speed devices to your computer while helping to protect you from harmful bacteria.

### Features

#### Durable USB-A to USB-B Cable Transfers Important Data at USB 2.0 Speeds

This USB cable (M/M) connects a printer, scanner, hub or other USB-B peripheral to the USB-A port on your computer or laptop. It transfers data at USB 2.0 speeds up to 480 Mbps for use with low-speed and high-speed devices, including multimedia applications. The cable is also backward compatible with earlier USB generations.

#### Provides Extra Protection Against Certain Bacteria

The molded connectors and PVC jacket are constructed using an antibacterial material that is effective in inhibiting the growth of *Escherichia coli* (E. coli) and *Staphylococcus aureus* (staph). This added protection makes this cable an ideal solution for medical facilities, schools, businesses, restaurants/kitchens and anywhere else that needs extra protection against bacteria.

#### Premium Construction for Superior Performance

Manufactured with twisted 28 AWG data lines and 24 AWG power lines, the U022AB-010-WH also features foil and braid shielding that ensures reliable, error-free signal quality and protection from EMI/RFI line noise that can distort or destroy data. Gold-plated connectors provide maximum conductivity and minimum data loss to guarantee a clear transmission free of interference. Integral strain relief gives the cable extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

#### White Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The cable has a white PVC jacket, which is easy to identify quickly in a crowded computer or hub and helps prevent the cable from becoming accidentally disconnected.

### Highlights

- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient data transfers
- Made with antibacterial material proven effective in inhibiting the growth of E. coli and staph
- Foil and braid shielding protects against EMI/RFI noise that can distort or destroy data
- Gold-plated connectors provide maximum conductivity and minimum data loss
- White jacket permits fast, easy identification in a crowded hub or computer

### Applications

- Connect a computer or laptop and a USB-B peripheral in a home or office network
- Provide extra protection against bacteria to give cable installers and IT personnel peace of mind during installation

### Package Includes

U022AB-010-WH USB-A to USB-B Antibacterial Cable (M/M), White, 10-ft. (3.05 m)

## Specifications

| OVERVIEW   |                      |
|------------|----------------------|
| UPC Code   | 037332260680         |
| Technology | USB 2.0 (High Speed) |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                              |
|--------------------------------------|------------------------------|
| Cable Type                           | Passive                      |
| <b>CONNECTIONS</b>                   |                              |
| Side A - Connector 1                 | USB A (MALE)                 |
| Side B - Connector 1                 | USB B (MALE)                 |
| Connector Plating                    | Gold                         |
| Contact Plating                      | Gold                         |
| Connector Style                      | Straight                     |
| <b>PHYSICAL</b>                      |                              |
| Material of Construction             | PVC                          |
| Cable Jacket Color                   | White                        |
| Cable Jacket Material                | PVC                          |
| Cable Jacket Rating                  | VW-1                         |
| Cable Outer Diameter (OD)            | 4.5MM                        |
| Wire Gauge (AWG)                     | 28/24                        |
| Cable Length (ft.)                   | 10                           |
| Cable Length (m)                     | 3.05                         |
| Cable Length (in.)                   | 120                          |
| Shipping Dimensions (hwd / in.)      | 9.00 x 7.00 x 0.50           |
| Shipping Dimensions (hwd / cm)       | 22.86 x 17.78 x 1.27         |
| Shipping Weight (lbs.)               | 0.23                         |
| Shipping Weight (kg)                 | 0.10                         |
| Unit Packaging Type                  | Polybag                      |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range            | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |
| Antimicrobial                        | No                           |
| USB Specification                    | USB 2.0 (up to 480 Mbps)     |
| Antibacterial                        | Yes                          |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                              |
| Product Compliance                   | RoHS; REACH                  |



Powering Business Worldwide

TRIPP LITE  
SERIES

WARRANTY & SUPPORT

Product Warranty Period  
(Worldwide)

Lifetime limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.