



Powering Business Worldwide

TRIPP LITE  
SERIES

## USB 3.2 Gen 1 SuperSpeed Device Cable (A to B M/M), 15 ft. (4.57 m)

MODEL NUMBER: U322-015



Allows connection between USB 3.2 Gen 1 Computers to USB 3.2 Gen 1 enabled Peripherals

### Features

- 15-ft. (4.57 m) USB 3.2 Gen 1 SuperSpeed cable
- SuperSpeed USB is 10 times faster than Hi-Speed USB, with transfer rates up to 5 Gbps.
- SuperSpeed USB is a Sync-N-Go technology that minimizes user wait-time.
- SuperSpeed USB will provide Optimized Power Efficiency...No device polling and lower active and idle power requirements.
- SuperSpeed USB is backwards compatible with USB 2.0. Devices interoperate with USB 2.0 platforms. Hosts support USB 2.0 legacy devices.

## Specifications

| OVERVIEW             |              |
|----------------------|--------------|
| UPC Code             | 037332158079 |
| Technology           | USB 3.x      |
| Cable Type           | Passive      |
| CONNECTIONS          |              |
| Side A - Connector 1 | USB A (MALE) |
| Side B - Connector 1 | USB B (MALE) |
| Connector Plating    | Nickel       |
| Contact Plating      | Gold         |
| Connector Style      | Straight     |

### Highlights

- 15ft SuperSpeed USB 3.2 Gen 1 A-B Cable
- 10 times faster than USB 2.0, with transfer rates up to 5 Gbps

### System Requirements

- Computers and Peripherals with USB 3.2 Gen 1 capabilities

### Package Includes

- 15-ft. (4.57 m) USB 3.2 Gen 1 SuperSpeed A-B Device cable



Powering Business Worldwide

TRIPP LITE  
SERIES

| PHYSICAL                            |                                     |
|-------------------------------------|-------------------------------------|
| Material of Construction            | PVC                                 |
| Cable Jacket Color                  | Blue                                |
| Cable Jacket Rating                 | VW-1                                |
| Cable Outer Diameter (OD)           | 5.5MM                               |
| Cable Length (ft.)                  | 15                                  |
| Cable Length (m)                    | 4.57                                |
| Cable Length (in.)                  | 180                                 |
| Shipping Dimensions (hwd / in.)     | 7.00 x 9.00 x 0.50                  |
| Shipping Dimensions (hwd / cm)      | 17.78 x 22.86 x 1.27                |
| Shipping Weight (lbs.)              | 0.04                                |
| Shipping Weight (kg)                | 0.02                                |
| ENVIRONMENTAL                       |                                     |
| Operating Temperature Range         | 14° to 140°F (-10° to 60°C)         |
| Storage Temperature Range           | -4° to 185°F (-20° to 85°C)         |
| Relative Humidity                   | 10% to 85%, Non-Condensing          |
| FEATURES & SPECIFICATIONS           |                                     |
| USB Specification                   | USB 3.2 Gen 1 (up to 5 Gbps)        |
| STANDARDS & COMPLIANCE              |                                     |
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT                  |                                     |
| Product Warranty Period (Worldwide) | Lifetime limited warranty           |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.