

## USB-C Cable (M/M) - USB 3.2 Gen 1 (5 Gbps), Thunderbolt 3 Compatible, Right-Angle Plug, 2 m (6.6 ft.)

MODEL NUMBER: U420-02M-RA



USB cable with right-angle plug connects a smartphone or other USB-C device to the USB-C port on your computer, charger or power bank.

### Features

#### USB-C Cable Connects Devices for Charging or Transferring Data at 5 Gbps Speeds

This USB cable (M/M) is compatible with any device with a USB-C or Thunderbolt 3 port, including MacBook Pros, Chromebooks and Windows laptops. It allows you to connect your notebook computer to a docking station, your Apple or Android smartphone to a wall charger or power bank, or an external hard drive to a PC or tablet, to name just a few valuable uses for the cable. It supports USB 3.2 Gen 1 data transfer speeds up to 5 Gbps, which is 10 times faster than USB 2.0.

#### PD Charging Cable Supports up to 60W for Syncing and Charging Mobile Devices

The Power Delivery cable provides power output up to 20V 3A (60W), which is sufficient for fast charging, syncing and powering most smartphones and other mobile devices.

#### Right-Angle Plug Makes Connecting in Tight Spaces Easier

A space-saving right-angle USB-C connector is easy to install in confined spaces, such as behind your computer or workstation. The right-angle construction also helps relieve strain on the cable and connector and prevents the cable from bending awkwardly.

#### Reversible USB-C Connectors Attach in Either Direction

Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connectors plug into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time.

### Highlights

- Power Delivery cable supports 20V 3A (60W) power output for charging host device
- Supports USB 3.2 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Reversible USB-C plugs connect in either direction for immediate no-fuss use
- Space-saving right-angle USB-C plug allows easy connection in confined spaces
- USB-C to USB-C cable is compatible with all USB-C and Thunderbolt 3 devices

### Applications

- Charge and power your MacBook Pro, Windows laptop or other USB-C or Thunderbolt 3 device from a USB-C wall charger
- Transfer data between an external hard drive and your laptop or PC
- Connect your laptop to a docking station or hub with a USB-C or Thunderbolt 3 port

### System Requirements

Devices with USB-C or Thunderbolt 3 ports (USB 3.2 Gen 1 compatibility required to achieve USB 3.2 Gen 1 speeds)

### Package Includes

U420-02M-RA USB-C to USB-C Cable, M/M, Black, 2 m (6.6 ft.)

## Specifications

| OVERVIEW   |                      |
|------------|----------------------|
| UPC Code   | 037332263667         |
| Technology | Thunderbolt; USB 3.x |
| Cable Type | Passive              |



Powering Business Worldwide

TRIPP LITE  
SERIES

| INPUT                                    |                                                            |
|------------------------------------------|------------------------------------------------------------|
| Maximum Input Amps                       | 3                                                          |
| Maximum Input Watts                      | 60                                                         |
| POWER                                    |                                                            |
| USB Power Delivery (PD) Charging Support | Yes                                                        |
| CONNECTIONS                              |                                                            |
| Side A - Connector 1                     | USB C (MALE) - RIGHT ANGLE                                 |
| Side B - Connector 1                     | USB C (MALE)                                               |
| Connector Plating                        | Nickel                                                     |
| Contact Plating                          | Gold                                                       |
| Connector Style                          | Angled                                                     |
| PHYSICAL                                 |                                                            |
| Material of Construction                 | PVC                                                        |
| Cable Jacket Color                       | Black                                                      |
| Cable Jacket Material                    | PVC                                                        |
| Cable Jacket Rating                      | VW-1                                                       |
| Cable Outer Diameter (OD)                | 4.5 mm                                                     |
| Cable Length (ft.)                       | 6.6                                                        |
| Cable Length (m)                         | 2.01                                                       |
| Cable Length (in.)                       | 78.7                                                       |
| Shipping Dimensions (hwd / in.)          | 0.60 x 7.00 x 9.75                                         |
| Shipping Weight (kg)                     | 0.09                                                       |
| Unit Packaging Type                      | Polybag                                                    |
| ENVIRONMENTAL                            |                                                            |
| Operating Temperature Range              | 14° to 140°F (-10° to 60°C)                                |
| Storage Temperature Range                | -4° to 158°F (-20° to 70°C)                                |
| Operating Humidity Range                 | 10% to 85% RH, Non-Condensing                              |
| Storage Humidity Range                   | 10% to 85% RH, Non-Condensing                              |
| Power Provided to Connected Device(s)    | 60W (20V/3A)                                               |
| FEATURES & SPECIFICATIONS                |                                                            |
| USB Specification                        | USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) |



Powering Business Worldwide

TRIPP LITE  
SERIES

| STANDARDS & COMPLIANCE              |                                     |
|-------------------------------------|-------------------------------------|
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT                  |                                     |
| Product Warranty Period (Worldwide) | 3-year limited warranty             |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.