

Be Your Window To The World

Der MSI PRO MP245PG FHD-Monitor mit HDMI und DisplayPort-Schnittstellen ist durch das IPS-Panel für beste Bild- und Farbqualität optimiert. Er wurde für die professionelle Arbeit in den Bereichen Programmierung, Codierung und Website-Design entwickelt. Er zeigt nicht nur jede Zeile und jedes Detail für Ihre Projekte klar und deutlich, sondern mit ihm lässt Sie auch reibungsloseste Streaming- und Videoerlebnisse genießen.



SELLING POINTS

- Perfekte 23,8" Bildschirmgröße für Programmieren, Codieren und Webdesign.
- TÜV-zertifiziertes Display sorgt für Schutz und Gesundheit der Augen.
- MSI EyesErgo-Technologie mit Anti-Flicker- und Weniger-Blaulicht-Technologie hilft, Augenbelastung und Ermüdung zu verhindern.
- 100 Hz Bildwiederholfrequenz bietet ein besseres Seherlebnis mit flimmerfreiem Bild.
- MSI Eye-Q Check hilft, die Augen selbst zu überprüfen und erinnert daran, Pausen einzulegen, wenn der Monitor längere Zeit benutzt wird.
- Der Monitorfuß ermöglicht Neigungs-, Dreh-, Höhen- und Schwenkeinstellungen.
- Vielseitigkeit bei verschiedenen Geräten durch Nutzung mehrerer Eingangsquellen wie HDMI™, DisplayPort und D-Sub(VGA)-Anschlüsse.
- VESA-montierbares Design.
- Eingebaute Lautsprecher.
- Nachhaltiges Produktdesign.



1. 1x Stromanschluss
2. 1x DisplayPort (1.2a)
3. 1x HDMI™ 1.4b (FHD@100Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Kopfhörerausgang
7. 1x Kensington Lock
8. 1x 5-Wege Navigation



PRO MP245PG

PRO MP245PG

SPECIFICATION

Model	SKU Number	9S6-3PC19M-005
	Entity MKT Name	PRO MP245PG
	Part No	9S6-3PC19M-005
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60cm)
	Active Display Area (mm)	527(H) x 296(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48 ~ 100Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.416~112.5 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	89/84
	NTSC (CIE1931 area percentage/overlap)	77/75
	sRGB (CIE1976 area percentage/overlap)	102/94
	sRGB (CIE1931 area percentage/overlap)	108/98
	Adobe RGB (CIE1976 area percentage/overlap)	87/84
	Adobe RGB (CIE1931 area percentage/overlap)	80/77
	DCI-P3 (CIE1976 area percentage/overlap)	81/80
	DCI-P3 (CIE1931 area percentage/overlap)	80/80
	Rec.709 (CIE1976 area percentage/overlap)	102/94
	Rec.709 (CIE1931 area percentage/overlap)	108/98
	Rec.2020 (CIE1976 area percentage/overlap)	59/59
	Rec.2020 (CIE1931 area percentage/overlap)	57/57
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Schnittstellen	D-Sub	1
	Line-in	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2
	DisplayPort HDCP version	1.3
Garantie	Warranty	24 Monate Pick-Up & Return
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	N/A
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



PRO MP245PG

PRO MP245PG

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	539.8 x 228.9 x 400.8
	Product Dimension without Stand (WxDxH) (mm)	539.8 x 53.3 x 319.7
	Stand Dimension (WxDxH) (mm)	224.2 x 228.9 x 403.4
	Weight (Net kg)	4.62
	Weight Without Stand (kg)	2.76
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.5 x 50.5
	Outer Carton Dimension (WxDxH) (cm)	61.8 x 14.3 x 53.5
	Weight (Gross kg)	7
Barcode Info	EAN	4711377211086