



ENTRY-LEVEL 3-PHASE POWER DISTRIBUTION

Provides reliable power distribution from 3-phase input source for connected equipment


Ideal for server room and IT applications, the Basic PDU (3-Phase) Series is a power distribution device that delivers electricity from a 3-phase power source to multiple devices. The products can work under high temperature, and also feature overload protection, external site ground pin, industrial-grade metal housing, adjustable mounting brackets, long input power cord, cord retention tray and IEC receptacle locking.

SERIES FEATURES

- Work under High Temperature
- Industrial-grade Metal Housing
- Adjustable Mounting Brackets
- Cord Retention Tray
- IEC Receptacle Locking

PRODUCT CALLOUTS

- 1 . AC Power Cord
- 2 . AC Outlets
- 3 . Circuit Breaker
- 4 . Cord Retention Tray Screw Holes



PDU13401



TECHNICAL SPECIFICATIONS

Model Name	PDU13401
Input	
Nominal Input Voltage (Vac)	346 - 415
Input Frequency (Hz)	50 / 60
Maximum Input Current (A)	16(CE)
Input Connector Type	IEC 60309 16A RED x 1
Power Cord Length (m.)	3.05
Output	
Outlet(s) - Total	42
Outlet(s) - Front	42
Outlet Type	IEC C13 x 36, IEC C19 x 6
Physical	
Installed Rack Height (U)	0
Cord Retention Tray	Yes
IEC Receptacle Locking	Yes
Physical Size	
Dimensions (WxHxD) (mm.)	56 x 1790 x 55
Weight (kg.)	5.8
Environmental	
Operating Temperature (°C)	-5 - 55
Operating Relative Humidity (Non-condensing) (%)	0 - 95
Certifications	
Certifications*	CE, EN 55032 Class A
RoHS	Yes

*Certifications may vary according to different regions. Visit www.cyberpower.com for more information.
 #All specifications are subject to change without notice.