集团微信订阅号 集团微信服务号

Pony Testing International Group

Report No.: MQI8TVJG2246707U3

2023 年 1 月 1 日生效

MSDS Report

Sample Name & Model	Li-MnO_2 Button cell CR2025
Applicant	Liyuan Battery Technology (Shenzhen) Co. LTD
Address	Building B, Gushu Hongwan Joint Stock Company, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen

No.: MQI8TVJG2246707U3
Code: oCZP74o7

PONY TESTING GROUP 深圳市普尼测试集团有限公司 PONY TESTING CO. LTD. SHENZHEN

PONY 普尼测试 Pony Testing International Group
Hotline 400-819-5688 www.ponytest.com

北京实验室：(010) 83055000 郑州实验室：(0371)69350670 成都普尼计量实验室：(028) 87702708 宁波实验室：(0574) 87736499
北京普尼科技公司：(010) 80415661 郑州普尼职业卫生公司：(0371) 80967099 贵州实验室：(0851) 85221000 合肥实验室：(0551) 63843474
北京普尼计量实验室：(010) 82492998 新疆实验室：(0991)6684186 上海实验室：(021) 64851999 深圳实验室：(0755) 26050909
青岛实验室：(0532) 88706866 石家庄实验室：(0311)85376660 苏州实验室：(0512) 62997900 深圳普尼计量实验室：(0755) 26050909-846
天津实验室：(022) 23607888 西安实验室：(029)89608785 苏州汽车座椅实验室及儿童安全座椅 普尼深圳通测：(0755) 27673339
长春实验室：(0431) 80530198 西安创纪检测科技有限公司：(029) 81123093 碰撞实验室：(0512) 62997900 广州实验室：(020) 89224310
沈阳实验室：(024) 22811886 西安普纳威检测技术公司：(029) 85729073 武汉实验室：(027) 83997127 南宁实验室：(0771) 5518818
大连实验室：(0411) 87336618 呼和浩特实验室：(0471) 3450025 武汉车附所：(027) 82318175 厦门实验室：(0592) 5568048
哈尔滨实验室：(0451) 58627755 成都实验室：(028)87702708 杭州实验室：(0571) 87219096

声 明
Statement

1. 本证明/报告的结论仅对委托方所送样品负责。
   The conclusion of the certificate/report is responsible for the provided sample only.

2. 委托方必须如实提供样品，申报和声明资料，并保证与实际相符，否则由委托方承担由此导致的全部后果和责任。
   The applicant shall provide accurately and truly the description and statement of the sample, shall guarantee to match the sample and real situation which they provided and declared. Otherwise the application shall bear any relevant consequences and responsibility.

3. 如委托方提供的样品及相关资料存在虚假、伪造等情形，所造成的全部后果和责任由委托方承担。
   In case the sample and documents provided involved in the situation of fake and forgery, any consequences and responsibility caused by this shall be undertaken by applicant.

4. 本证明/报告私自转让、盗用、冒用、涂改、未经本单位批准的复制（全文复制除外）或以其它任何形式的篡改均属无效，本单位将对上述行为严究其相应的法律责任。
   The certificate/report is invalid in case of illegal transfer, embezzlement, imposture, modification or any altering, reproducing except in full, without approval of PONY. PONY shall investigate and affix the applicant's legal liability accordingly.

5. 本证明/报告不考虑国家及经营人差异。
   The certificate/report takes no account of the differences of countries and applicants.

6. 本单位有权在完成证明/报告后处理委托方所送样品。
   PONY has the right to dispose the provided sample after approval of the certificate/report.

▲防伪说明：

(1) 报告编号是唯一的；

(2) 报告采用特制防伪纸张印制，纸张表面带有“PONY”防伪纹路，该防伪纹路不支持复印，即复制件不会带有“PONY”防伪纹路；

(3) 报告采用的防伪纸张内部亦加带有高科技“PONY”防伪水印，只有在验钞机等紫外线照射下方可显出无色荧光防伪字样。

全国服务热线
400-819-5688
WWW.PONYTEST.COM

集团微信订阅号 集团微信服务号

北京实验室：(010) 83055000
北京谱尼科技公司：(010) 80415661
北京谱尼计量实验室：(010) 82492998
青岛实验室：(0532) 88706866
天津实验室：(022) 23607888
长春实验室：(0431) 80530198
沈阳实验室：(024) 22811886
大连实验室：(0411) 87336618
哈尔滨实验室：(0451) 58627755
郑州实验室：(0371) 69350670
郑州谱尼职业卫生公司：(0371) 80967099
新疆实验室：(0991) 6684186
石家庄实验室：(0311) 85376660
西安实验室：(029) 89608785
西安创尼信息科技有限公司：(029) 81123093
西安查德威克检测技术公司：(029) 85729073
呼和浩特实验室：(0471) 3450025
成都实验室：(028) 87702708
成都谱尼计量实验室：(028) 87702708
贵州实验室：(0851) 85221000
上海实验室：(021) 64851999
苏州实验室：(0512) 62997900
苏州汽车座椅实验室及儿童安全座椅碰撞实验室：(0512) 62997900
武汉实验室：(027) 83997127
武汉车附所：(027) 82318175
杭州实验室：(0571) 87219096
宁波实验室：(0574) 87736499
合肥实验室：(0551) 63843474
深圳实验室：(0755) 26050909
深圳谱尼计量实验室：(0755) 26050909-846
谱尼深圳通测：(0755) 27673339
广州实验室：(020) 89224310
南宁实验室：(0771) 5518818
厦门实验室：(0592) 5568048

集团微信订阅号 集团微信服务号

Pony Testing International Group

Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.9 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification

Sample Name: Li-MnO_2 Button cell

Sample Model: CR2025

Recommended Uses: N/A

Restrictions on Use: N/A

Supplier Name: Liyuan Battery Technology (Yichun) Co. LTD

Address: 166, Food Avenue, Shanggao County Industrial Park, Yichun City, Jiangxi

Phone Number: 13554721711

FAX: 0755-29887011

E-mail: xuliqing@liyuancell.com

Emergency Phone Number: 0755-29887011

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxicity, oral (4)

Acute toxicity, inhalation (4)

Skin corrosion/irritation (1A-1C)

Serious eye damage/eye irritation (1)

Sensitisation, skin (1, 1A, 1B)

Carcinogenicity (2)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Specific target organ toxicity, repeated exposure (2)

Label elements

Hazard pictogram(s):

Signal word: Danger

Hazard statement(s):

H302 Harmful if swallowed

H332 Harmful if inhaled

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer

H335 May cause respiratory irritation

H373 May cause damage to organs through prolonged or repeated exposure

Precautionary statement(s):

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust, fume, gas, mist, vapours, spray.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

Response:

P330 Rinse mouth.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P363 Wash contaminated clothing before reuse.

P310 Immediately call a POISON CENTER.

P321 Specific treatment (See additional emergency instructions).

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302 + P352 IF ON SKIN: Wash with plenty of water.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Stainless steel	12597-68-1	603-108-1	49.66
Manganese dioxide	1313-13-9	215-202-6	30.99
Carbon black	1333-86-4	215-609-9	2.17
Graphite	7782-42-5	231-955-3	2.17
Polytetrafluoroethylene resin	9002-84-0	618-337-2	0.77
Lithium	7439-93-2	231-102-5	2
Lithium Perchlorate	7791-03-9	232-237-2	4
1,2-Propanediolcyclic carbonate	108-32-7	203-572-1	3
Ethylene glycol dimethyl ether	110-71-4	203-794-9	1.48
Polypropylene	9003-07-0	618-352-4	3.76

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, soda ash, lime or sand. Large Fire: DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media:

Water or foam.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Produce flammable gases on contact with water. May ignite on contact with water or moist air. Some react vigorously or explosively on contact with water. May be ignited by heat, sparks or flames. May re-ignite after fire is extinguished. Runoff may create fire or explosion hazard.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate the area before entry.

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do it without risk. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. DO NOT GET WATER on spilled substance or inside containers. Small Spill: Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Dike for later disposal; do not apply water unless directed to do so. Powder Spill: Cover

powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handing must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
12597-68-1	N/A	N/A	N/A
1313-13-9	N/A	N/A	N/A
1333-86-4	TLV-TWA 3mg/m^3	REL-TWA 3.5mg/m^3	PEL-TWA 3.5mg/m^3
7782-42-5	TLV-TWA 2mg/m^3	REL-TWA 2.5mg/m^3	PEL-TWA 15mppcf PEL-TWA 20mppcf
9002-84-0	N/A	N/A	N/A
7439-93-2	N/A	N/A	N/A
7791-03-9	N/A	N/A	N/A
108-32-7	N/A	N/A	N/A
110-71-4	N/A	N/A	N/A

9003-07-0	N/A	N/A	N/A

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Colour:	Silver.
Physical State:	Button.
Odour:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Boiling point or initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Flammability:	Not available.
Solubility:	Not available.
Lower and upper explosion limit/flammability limit:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Kinematic viscosity:	Not available.
Partition coefficient: n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Density and/or relative density:	Not available.

Relative vapour density:	Not available.
Particle characteristics:	Not available.
Other information:	
Voltage	3.0V
Electric capacity	150mAh
Aggregate lithium content	0.045g

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
12597-68-1	No data available.
1313-13-9	No data available.
1333-86-4	No data available.
7782-42-5	No data available.
9002-84-0	No data available.
7439-93-2	No data available.
7791-03-9	No data available.
108-32-7	LD50 Rat (oral): ⩾29000mg/kg; LD50 Rabbit (Dermal): >20000mg/kg
110-71-4	LD50 Rat (oral): 2525mg/kg
9003-07-0	No data available.

Skin corrosion/irritation: No data available.

Serious eye damage/irritation: No data available.

Respiratory or Skin sensitization: No data available.

Germ Cell mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive toxicity: No data available.

Specific target organ toxicity-Single exposure: No data available.

Specific target organ toxicity-Repeated exposure: No data available.

Aspiration hazard: No data available.

Information on the likely routes of exposure: No data available.

Eye: No data available.

Skin: No data available.

Ingestion: No data available.

Inhalation: No data available.

Section 12 - Ecological Information

Ecological Toxicity:

CAS# 108-32-7

LC50: >1000 mg/L - Fish (Carp) - 96h;

EC50: >1000 mg/L - Crustaceans (Daphnia magna) - 48h;

EC50: >900 mg/L - Algae (Scenedesmus subspicatus) - 72h

Persistence and degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other adverse effects: No data available.

Section 13 - Disposal Considerations

Disposal methods:

Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN or ID Number

IATA	UN3090
IMDG	UN3090
Proper Shipping Name/Description	
IATA	Lithium metal batteries
IMDG	LITHIUM METAL BATTERIES
Class or Div. (Sub Hazard)	
IATA	9
Packing Group	
IATA	N/A
IMDG	N/A
Hazard Label	
IATA	
IMDG	N/A
Environmental hazards	
Marine pollutant:	No
IMDG EmS:	F-A. S-I
Special precautions for user	No information available.

Transport information: The Li-MnO_2 Button cell CR2025 has passed the test UN38.3, according to the report ID: MPI83PTL733887U5.

According to the Packing Instruction 968 section IB of IATA DGR 64th Edition for transportation, Cargo aircraft only.

According to the special provision 188 of IMDG (40-20), the goods are not subject to other provision of this code.

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Transport Fashion: By air, by sea.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
12597-68-1	Listed	Listed	Listed DSL	Listed
1313-13-9	Listed	Listed	Listed DSL	Listed
1333-86-4	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
9002-84-0	Listed	Listed	Listed DSL	Listed
7439-93-2	Listed	Listed	Listed DSL	Listed
7791-03-9	Listed	Listed	Listed DSL	Listed
108-32-7	Listed	Listed	Listed DSL	Listed
110-71-4	Listed	Listed	Listed DSL	Listed
9003-07-0	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Date: 2022-12-19

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);

STEL: (Short Term Exposure Limit);

PEL: (Permissible Exposure Level);
REL: (Recommended Exposure Limit);
PC-STEL: (Permissible concentration-short time exposure limit);
PC-TWA: (Permissible concentration-time weighted average);
IARC: (International Agency for Research on Cancer);
LC50: (Lethal concentration, 50 percent kill);
LD50: (Lethal dose, 50 percent kill);
EC50: (Median effective concentration);
BCF: (Bioconcentration Factor);
BOD: (Biochemical oxygen demand);
IECSC: (Inventory of Existing Chemical Substances in China);
NOEC: (No observed effect concentration);
NTP: (US National Toxicology Program);
RTECS: (Registry of Toxic Effects of Chemical Substances);
TOC: (Total Organic Carbon);
TSCA: (Toxic Substances Control Act of USA);
DSL: (the Domestic Substances List of Canada);
NDSL: (the Non-domestic Substances List of Canada);
IATA: (International Air Transport Association);
IMDG: (International Maritime Dangerous Goods);
TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations)

End of report