PEN DISPLAY

# XF2230

## Key **Features**

- IP65 Dustproof & Water-resistant Screen
- 10-point PCAP Touch Technology
- 24/7 Operation
- MoHs 7 Scratch-Resistant Surface
- VESA-mountable




## Product **Description**

The ViewSonic XF2230 is an open-frame monitor designed for commercial and industrial applications, such as library check-out and return kiosks, ensuring reliable 24/7 operation. Its durable 3mm thick glass screen protects against moisture and scratches, ensuring long-lasting performance. The intuitive 10-point PCAP touch technology delivers smooth, responsive interaction, enhancing the user experience. With versatile connectivity options, including HDMI, DisplayPort, and VGA, content sharing is simple and seamless. The VESA-compatible design allows for flexible installation on any surface or orientation. Optional features include a wide operating temperature range from -10°C to 80°C for demanding environments.

1. VESA Compatible(Wall Mount 75 x 75 mm & 100 x 100 mm)
2. Menu Control Panel
3. USB
4. DC12V
5. HDMI
6. DP
7. VGA
8. PC IN

**Visit Us** www.viewsonic.com

## DISPLAY

| | |
|---|---|
| Aspect Ratio: | 16:9 |
| Screen Size: | 21.5" |
| Active Area: | 476.06 (H) x 267.79 (V) |
| Pixel Pitch (mm): | 0.25 (H) x 0.25 (V) |
| Resolution: | 1920 x 1080 |
| Contrast Ratio: | 1000:1 |
| Brightness: | 210 cd/m² |
| Viewing Angles: | H:178° V:178° |
| Response Time: | 22 ms |
| Display Colors: | 16.7 M |
| Backlight Life: | 50,000 hrs |
| Color Gamut: | NTSC 72% |
| Surface Treatment: | Hard coating (7H) |
| Cover Glass Thickness: | 3 mm |
| Touch Screen: | PCAP 10 points |

## COMPATIBILITY

| | |
|---|---|
| PC Resolution (max): | 1920 x 1080 |
| Mac Resolution (max): | 1920 x 1080 |
| Operating System: | Windows & macOS |

## CONNECTOR

| | |
|---|---|
| USB 2.0 Type-B: | 1 (for touch screen only) |
| 3.5mm Audio in: | 1 |
| HDMI: | 1 |
| DisplayPort: | 1 |
| VGA: | 1 |
| Power In: | DC socket |

## POWER

| | |
|---|---|
| Power Consumption (typical): | 20.34 W |
| Power Consumption (max): | 22.34 W |
| Stand-by: | 1.69 W |
| Voltage: | AC 100 - 240V, DC 12V/4A |

## CONTROLS

| | |
|---|---|
| Physical Controls: | Auto, Menu, Left, Right, Exit, Power |
| OSD: | Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Reset |

## OPERATING CONDITIONS

| | |
|---|---|
| Temp. (operating): | 0 - 50˚C (Non-condensation) |
| Temp. (storage): | -20 - 60˚C (Non-condensation) |
| Humidity: | 5-90 (%RH) |

## WALL MOUNT

| | |
|---|---|
| VESA Compatible: | 75 x 75 mm & 100 x 100 mm |

## DIMENSIONS

| | |
|---|---|
| Physical (W x H x D): | 511.9 x 303.4 x 47.8 mm |
| Box (W x H x D): | 585 x 440 x 130 mm |

## WEIGHT

| | |
|---|---|
| Net (kg/lb): | 4.9 kg / 10.8 lb |
| Gross (kg/lb): | 6.2 kg / 13.7 lb |

## FRONT TOUCHSCREEN PROTECTION

| | |
|---|---|
| IP65: | Yes |
| IK08: | Yes |

## ADD-ON (PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE FOR DETAILS.)

| | |
|---|---|
| Stylus: | Optional |
| Wide Temperature: | Optional |
| Light Sensor: | Optional |

## GENERAL

| | |
|---|---|
| Package Contents: | HDMI cable x1, USB A/B cable x1, 3-pin power cord x1, Quick start guide x1, AC/DC adapter x1 |
| Regulation / Compliance: | cTUVus, FCC, CE, CB, RoHS, VCCI, PSE, BIS, ErP |

Copyright © ViewSonic Corporation 2000-2026. All rights reserved.