

Business & Productivity Monitor

Entdecken Sie unseren PerfectEdge Monitor PRO MP272PMG mit integrierter Webcam, der entwickelt wurde, um strengen Umweltstandards zu entsprechen und eine sauberere, grünere Welt zu gewährleisten. Mit EyesErgo und einem vollergonomischen Standfuß steht alles für das Wohlbefinden der Nutzer bereit.



SELLING POINTS

- Integrierte FHD-Webcam mit digitalem Mikrofon und Webcam-Abdeckung
- TÜV-zertifiziertes Display sorgt für den Schutz und die Gesundheit der Augen.
- MSI EyesErgo-Technologie mit Anti-Flicker-Technologie hilft, Augenbelastung und Ermüdung zu vermeiden.
- Die Bildwiederholrate von 120 Hz bietet ein besseres Seherlebnis mit flimmerfreiem Bild.
- MSI Eye-Q Check hilft bei der Selbstkontrolle der Augen und erinnert daran, bei längerer Nutzung des Monitors Pausen einzulegen.
- Der Standfuß ist ergonomisch gestaltet und bietet Neigungs-, Schwenk-, Höhen- und Drehverstellung.
- Ein verstellbarer Standfuß mit mini-PC-montierbarem Design sorgt für eine bessere Ergonomie und einen aufgeräumten Arbeitsplatz, was den Benutzerkomfort und die Organisation verbessert.
- Standard-VESA-kompatibel und mit Zubehörsteckplatz ausgestattet.
- Zwei integrierte Lautsprecher.



1. 5-Wege Navigation
2. Stromanschluss
3. 1x Kopfhöreranschluss
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@120Hz)
6. 1x D-Sub (VGA)
7. 2x USB 2.0 Typ-A
8. 1x USB 2.0 Typ-B
9. Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3PD99T-001
	Entity MKT Name	PRO MP272PMG
	Part No	9S6-3PD99T-001
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888 (H) x 336.312 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	47.11~144.23 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	101%/82%
	NTSC (CIE1931 area percentage/overlap)	81%/74%
	sRGB (CIE1976 area percentage/overlap)	116%/99%
	sRGB (CIE1931 area percentage/overlap)	114%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	100%/86%
	Adobe RGB (CIE1931 area percentage/overlap)	84%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	93%/90%
	DCI-P3 (CIE1931 area percentage/overlap)	84%/83%
	Rec.709 (CIE1976 area percentage/overlap)	116%/99%
	Rec.709 (CIE1931 area percentage/overlap)	114%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	60%/60%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Schnittstellen	D-Sub	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Lock type	Kensington Lock
	Speaker	2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Garantie	Warranty	36 Monate Pick-Up & Return
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	20 (SDR) 25 (HDR)
	Annual Energy Consumption (KWh)	65
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) F (HDR)
	Power Cord Type	C13

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	612 x 227 x 429
	Product Dimension without Stand (WxDxH) (mm)	612 x 46 x 357
	Stand Dimension (WxDxH) (mm)	260 x 227 x 412
	Weight (Net kg)	6.2
	Weight Without Stand (kg)	3.5
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	83.9 x 13.1 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	85.4 x 14.6 x 47.1
	Weight (Gross kg)	8.5
Barcode Info	EAN	4711377260442