

## Slim, Sleek, Smooth

Entdecken Sie unseren 144Hz Commercial Monitor PRO MP275QDE E14 mit IPS-Panel, der für Ihre tägliche Arbeit und Unterhaltung konzipiert ist. Mit EyesErgo für das Wohlbefinden der Benutzer und einer Bildwiederholfrquenz von 144Hz, verbessern Sie ihr Bildschirmlebnis für alle Anwendungszwecke.



Picture and logos

## SELLING POINTS

- Genieße erstklassige Unterhaltung mit flüssigen 144 Hz.
- Das TÜV-zertifizierte Display schont deine Augen und unterstützt langfristige Augengesundheit.
- Die MSI EyesErgo- und Anti-Flicker-Technik reduziert Belastung und Ermüdung der Augen.
- MSI Eye-Q Check unterstützt dich bei der Selbstprüfung deiner Augen und erinnert dich bei längerer Nutzung an regelmäßige Pausen.
- Nutze HDMI™- und DP-Anschlüsse für flexible Verbindungen mit verschiedenen Geräten.
- Sorge für Ordnung mit dem praktischen, abnehmbaren Kabelmanagement.
- Standard-VESA-montierbar & Zubehörschlitz-Design.



1. 5-Wege Navi Tasten
2. Stromanschluss
3. 2x HDMI™ 2.0b (WQHD@144Hz)
4. 1x DisplayPort 1.2a
5. 1x Kopfhöreranschluss
6. Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3PF2CM-005
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/78%
	NTSC (CIE1931 area percentage/overlap)	78%/70%
	sRGB (CIE1976 area percentage/overlap)	115%/95%
	sRGB (CIE1931 area percentage/overlap)	110%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	95%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	80%/72%
	DCI-P3 (CIE1976 area percentage/overlap)	90%/85%
	DCI-P3 (CIE1931 area percentage/overlap)	80%/78%
	Rec.709 (CIE1976 area percentage/overlap)	115%/95%
	Rec.709 (CIE1931 area percentage/overlap)	110%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	65%/65%
	Rec.2020 (CIE1931 area percentage/overlap)	58%/58%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 45
	Outer Carton Dimension (WxDxH) (cm)	70.8 x 14.8 x 48
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377392792